

# ENVIRONMENTAL PRODUCT DECLARATION

in accordance with ISO 14025, ISO 21930 and EN 15804

Owner of the declaration:	Saint-Gobain Sweden AB, Scanspac
Program operator:	The Norwegian EPD Foundation
Publisher:	The Norwegian EPD Foundation
Declaration number:	NEPD-1923-848-EN
Registration number:	NEPD-1923-848-EN
ECO Platform reference number:	-
Issue date:	19.11.2019
Valid to:	19.11.2024

## Dalapro Premium, Roll Premium, Lightning Premium

Saint-Gobain Sweden AB, Scanspac

**Dalapro**<sup>®</sup>

[www.epd-norge.no](http://www.epd-norge.no)



**General information**

**Product:**

Dalapro Premium, Roll Premium, Lightning Premium

**Owner of the declaration:**

Saint-Gobain Sweden AB, Scanspac  
 Contact person: Christian Nilsson  
 Phone: +46 (0)19-46 34 00  
 e-mail: info@dalapro.se

**Program operator:**

The Norwegian EPD Foundation  
 Pb. 5250 Majorstuen, 0303 Oslo  
 Phone: +47 97722020

e-mail: [post@epd-norge.no](mailto:post@epd-norge.no)

**Manufacturer:**

Saint-Gobain Sweden AB, Scanspac

**Declaration number:**

NEPD-1923-848-EN

**Place of production:**

Saint Gobain Sweden AB, Scanspac  
 Site: Glanshammar, Kemivägen 7, 70597 Glanshammar, SWEDEN  
 Site: Sala, Norrängsgatan 35, 73338 Sala, SWEDEN

**ECO Platform reference number:**

**Management system:**

ISO 9001, ISO 14001

**This declaration is based on Product Category Rules:**

CEN Standard EN 15804:2012+A1:2013 serves as core PCR.  
 NPCR 009 version 1.0

**Organisation no:**

556241-2592

**Statement of liability:**

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

**Issue date:** 19.11.2019

**Valid to:** 19.11.2024

**Declared unit:**

1 kg Dalapro Premium, Roll Premium, Lightning Premium

**Year of study:**

2018

**Declared unit with option:**

A1,A2,A3,A4

**Comparability:**

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

**Functional unit:**

**Author of the Life Cycle Assessment:**

The declaration is developed using eEPD v3.0 from LCA.no  
 Approval:  
 Company specific data are:

Collected/registered by: Ellinor Johansson

Internal verification by: Christian Nilsson

**Verification:**

Independent verification of data, other environmental information and the declaration according to ISO14025:2010, § 8.1.3 and § 8.1.4

External

---

Third party verifier:


Sign



Senior Research Scientist, Anne Rønning  
 (Independent verifier approved by EPD Norway)

**Approved:**

Sign



Håkon Hauan  
 Managing Director of EPD-Norway

## Product

### Product description:

Dalapro Premium, Dalapro Roll Premium and Dalapro Lightning Premium is ready-mixed all-round fillers. The new recipe creates a lighter filler with even better filling capacity. For joint filling and thin smoothing on most surfaces such as plaster, concrete and woven glass fibre in new construction and renovation. The special consistency makes it easy to work with. The filler is white, providing a good base for over-painting with light colours. MATERIAL CONSUMPTION For joint filling on plasterboard: approx. 0.3 litres/metre.

For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.

### Product specification

Packaging: Dalapro Premium: 0.5-litre container, 3-litre and 10-litre plastic buckets. Dalapro Roll Premium: 12-litre plastic bucket and Dalapro Lightning Premium: 15 litre plastic bucket and 15L plastic bag.

All calculations of the packaging material is made with the 10 liter bucket that represent the majority of the market.

Materials	%
Filler Dolomite	30-40%
Water	30-50%
Filler Perlite	5-10%
Binder	2,5-10%
Thickener	0,5-5%
Additive	1-3%

### Technical data:

Binding agent: Latex co-polymer  
Solvent: Water  
Grain size: Max. 0.15 mm  
pH: Approx. 9  
Colour: White

### Market:

Europe

### Reference service life, product

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well.

### Reference service life, building

Not part of the declaration.

## LCA: Calculation rules

### Declared unit:

1 kg Dalapro Premium, Roll Premium, Lightning Premium

### Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

### Data quality:

Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Chemicals	Chemicals below cut-off	No data	0
Binder	ecoinvent 3.4	Database	2017
Cellulose Ether	ecoinvent 3.4	Database	2017
Chemicals	ecoinvent 3.4	Database	2017
Filler	ecoinvent 3.4	Database	2017
Packaging	ecoinvent 3.4	Database	2017
Water	ecoinvent 3.4	Database	2017
Packaging	Modified ecoinvent 3.4	Database	2017

### Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

System boundary:

A1



A2



A3



A4



**Additional technical information:**

Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When treating plasterboards, follow recommendations in accordance with EN 13963.

## LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

### Transport from production place to user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	55,0 %	Truck, lorry over 32 tonnes, EURO 5	300	0,022823	l/tkm	6,85
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

Assembly (A5)			Use (B1)			
.	Unit	Value	.	Unit	Value	
Auxiliary	kg					
Water consumption	m <sup>3</sup>					
Electricity consumption	kWh					
Other energy carriers	MJ					
Material loss	kg					
Output materials from waste treatment	kg					
Dust in the air	kg					
VOC emissions	kg					
Maintenance (B2)/Repair (B3)			Replacement (B4)/Refurbishment (B5)			
.	Unit	Value	.	Unit	Value	
Maintenance cycle*			Replacement cycle*			
Auxiliary			Electricity consumption	kWh		
Other resources			Replacement of worn parts			
Water consumption	m <sup>3</sup>		* Described above if relevant			
Electricity consumption	kWh					
Other energy carriers	MJ					
Material loss	kg					
VOC emissions	kg					
Operational energy (B6) and water consumption (B7)			End of Life (C1, C2)			
.	Unit	Value	.	Unit	Value	
Water consumption	m <sup>3</sup>		Hazardous waste disposed	kg		
Electricity consumption	kWh		Collected as mixed construction waste	kg		
Other energy carriers	MJ		Reuse	kg		
Power output of equipment	kW		Recycling			
			Energy recovery			
			To landfill	kg		
Transport to waste processing (C2)						
Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck					l/tkm	
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

Scenarios after A1-A4 are not included

LCA: Results

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage				Construction installation stage	User stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	

Environmental impact

Parameter	Unit	A1	A2	A3	A4
GWP	kg CO <sub>2</sub> -eq	3,05E-01	1,54E-02	4,41E-03	2,62E-02
ODP	kg CFC11 -eq	2,01E-08	1,66E-09	6,35E-10	5,10E-09
POCP	kg C <sub>2</sub> H <sub>4</sub> -eq	1,43E-04	5,68E-06	1,63E-06	4,23E-06
AP	kg SO <sub>2</sub> -eq	2,34E-03	1,61E-04	3,22E-05	8,51E-05
EP	kg PO <sub>4</sub> <sup>3-</sup> -eq	4,99E-04	1,68E-05	1,58E-05	1,43E-05
ADPM	kg Sb -eq	1,50E-06	2,77E-08	1,81E-08	5,91E-08
ADPE	MJ	6,05E+00	2,28E-01	4,15E-02	4,11E-01

GWP Global warming potential; ODP Depletion potential of the stratospheric ozone layer; POCP Formation potential of tropospheric photochemical oxidants; AP Acidification potential of land and water; EP Eutrophication potential; ADPM Abiotic depletion potential for non fossil resources; ADPE Abiotic depletion potential for fossil resources

Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009

\*INA Indicator Not Assessed

Resource use

Parameter	Unit	A1	A2	A3	A4
RPEE	MJ	1,51E+00	4,65E-03	2,61E-01	7,42E-03
RPEM	MJ	9,41E-01	0,00E+00	1,45E-04	0,00E+00
TPE	MJ	2,45E+00	4,65E-03	2,62E-01	7,42E-03
NRPE	MJ	6,96E+00	2,36E-01	4,40E-02	4,23E-01
NRPM	MJ	2,18E+00	0,00E+00	0,00E+00	0,00E+00
TRPE	MJ	9,14E+00	2,36E-01	4,40E-02	4,23E-01
SM	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
W	m <sup>3</sup>	3,71E-03	4,70E-05	4,85E-04	9,98E-05

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non renewable primary energy resources used as energy carrier; NRPM Non renewable primary energy resources used as materials; TRPE Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; W Use of net fresh water

Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009

\*INA Indicator Not Assessed

End of life - Waste

Parameter	Unit	A1	A2	A3	A4
HW	kg	4,59E-06	1,30E-07	1,69E-04	2,25E-07
NHW	kg	1,55E-01	1,39E-02	6,97E-03	3,84E-02
RW	kg	INA*	INA*	INA*	INA*

HW Hazardous waste disposed; NHW Non hazardous waste disposed; RW Radioactive waste disposed

Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009

\*INA Indicator Not Assessed

End of life - Output flow

Parameter	Unit	A1	A2	A3	A4
CR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MR	kg	0,00E+00	0,00E+00	7,61E-04	0,00E+00
MER	kg	0,00E+00	0,00E+00	9,79E-03	0,00E+00
EEE	MJ	INA*	INA*	INA*	INA*
ETE	MJ	INA*	INA*	INA*	INA*

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009

\*INA Indicator Not Assessed

## Additional Norwegian requirements

### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Renewable electricity with Guarantee of Origin from LOS (kWh)	Modified ecoinvent 3.4	60,20	g CO2-ekv/kWh

### Dangerous substances

The product contains no substances given by the REACH Candidate list or the Norwegian priority list.

### Indoor environment

Emission test performed by Eurofins according to the ISO 16000 standard.

## Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A1:2013 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works. Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2018) eEPD v3.0 - Background information for EPD generator system, LCA.no report number 04.18

Iversen et al., (2019) EPD generator for Saint-Gobain Weber and Scanspac - Background information and LCA data, LCA.no report number 05.18

NPCR Part A: Construction products and services. Ver. 1.0. April 2017, EPD-Norge.

NPCR 009 Part B for technical-chemical products. Ver. 1.0 June 2018, EPD-Norge.

 <b>epd-norge.no</b> The Norwegian EPD Foundation	<b>Program operator and publisher</b> The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo 0303 Oslo Norway	Phone: +47 97722020  e-mail: post@epd-norge.no web: www.epd-norge.no
 <b>Dalapro®</b>	<b>Owner of the declaration</b> Saint-Gobain Sweden AB, Scanspac Kemivägen 7 SE-705 97 Glanshammar	Phone: +46 (0)19-46 34 00 Fax: e-mail: info@dalapro.se web: www.dalapro.se
	<b>Author of the Life Cycle Assessment</b> LCA.no AS Dokka 1C 1671 Kråkerøy	Phone: +47 916 50 916 Fax: e-mail: post@lca.no web: www.lca.no
	<b>Developer of EPD generator</b> LCA.no AS Dokka 1C 1671 Kråkerøy	Phone: +47 916 50 916  e-mail: post@lca.no web: www.lca.no