

737 Wet Room Adhesive



Produktinformation

Beck & Jørgensen A/S

Product Description

The adhesive is a part of B&J Bathroom system. Information on www.bj.dk
Adhesive for wall covering of woven and non woven glass covering.
For gypsum board, plaster and concrete in dry rooms.

Directions for use

Indoors for woven and non woven glass covering on plasterboard, plaster, concrete and painted surfaces.
Absorbent and porous substrates are primed with Wet Room Primer 736 diluted with water (1 part primer to 3 parts water). The primer must be completely dry before the next application.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Personal protection equipment must be used. For information regarding safety, health and environment see Material Safety Data Sheet (MSDS) at www.bj.dk.

Remarks

For further working instructions, please contact B&J Technical Department.
Use eyeprotection and mask when sanding.

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Tekniske data

Bindemiddel:

MBK-Type: Adhesive, wet rooms

Glans:

Vol. tørstof:

Kulør: Colourless

Tørretid: 2-4 hours, recoatable after approx 24 hours at 20 °C 60% RH

Påføring: +10° C to +25° C. RH: 40-65%

Fortynding: Water

Rækkeevne:

Værktøj: Brush, roller or airless

Mal-Kode: 00-1 (1993)

